

Sport Farm Rules

Sport Farm Rules all safety rules will be exactly the same as in the Super Farm Class with the exception of: -

1. Maximum RPM 2500 (must be accessible for checking by the scrutineer);
2. OEM flywheels and clutches will be allowed;
3. Steel flywheel and clutch guarding will be allowed (10mm thick 360° around the bell housing to cover from front of flywheel to rear of clutch assembly);
4. A limited orifice on air intake of 55 mm diameter will be provided by the SWTPA;
5. Roll bars will be allowed (with the addition of two 50mm x 6mm straps across the rear of the seating area);
6. Homemade roll bars will be allowed (construction guidelines are as follows): If using a home made roll frame, it should be able to withstand the full weight of the tractor without major deformation. A minimum of 80 x 80 x 4.5mm box section, welded onto two 20mm thick fixing plates. Both plates must be fastened to the tractor with 4 M16 grade 8.8 bolts on the left and right trumpet housing.
7. Both diagonal parts must be a minimum of 700mm long, and the joint with the vertical bar should be above the rear tyres.
8. The top of the roll bar must not be more than 1.71m above the fixing plates.
9. Self build roll bars that are not to this minimum standard will need to show engineers calculations that are signed off as safe for this application. See examples and pictures below.
10. Weight classes will be 3.5 tonnes/4.5 tonnes;
11. Drivers attire, good clean overalls and safety footwear;

